Newtop Chemical Materials (Shanghai) Co.,Ltd.

Technical Indicators

FASCAT4210 catalyst dibutyl tin dichloride Arkema PMC

Overview:

Chinese name: FASCAT4210 Catalyst

Alias: Di-butyltin dichloride, di-butyltin dichloride, di-butyltin

dichloride, di-butyltin dichloride, di-butyltin dichloride,

di-butyltin dichloride

Physico-chemical properties:

CAS 683-18-1

EC 211-670-0

Molecular formula C8H18CI2SN

Molecular weight: 303.85

Character: white crystal. Sensitive to humidity and hydrolyzes in hot water. Soluble in

many organic solvents, insoluble in water. Relative density (d244)1.36. Melting point

39 ~ 41°C. Boiling point 135 ° C (1.33kPa). Refractive index (n51D)1.4991. Flash

point >112 ° C. Moderately toxic, median lethal dose (in rats, orally)100mg/kg.

Corrosive.

[Appearance properties] White crystal.

[Melting point] 39 °C

Boiling point 135 °C10 mm Hg(lit.)

[Density] 1.4

Newtop Chemical Materials (Shanghai) Co.,Ltd. Technical Indicators



【 Refractive index 】 1.4991

Flash point >230 °F

【 Storage condition 】 2-8°C

[water solubility] 320 mg/L, hydrolises in hot water

Uses:

Organic synthesis. Catalysts for polymerization. Organotin intermediates.



Leak treatment

Stop leaks as much as possible while ensuring safety. If a minor leak is found, treat it with sand or other absorbent material and place it in a clean, dry container for subsequent treatment. If a large amount of leakage occurs, the leaked material should

Newtop Chemical Materials (Shanghai) Co.,Ltd.

Technical Indicators

be collected for subsequent treatment. Avoid material entering groundwater or

surface water, because it is not easily degraded by biological matter. All collected

leakage materials should be disposed of in accordance with the relevant regulations of

the local environmental protection department.

Disclaimer

The information and technical advice provided above are obtained from reliable

sources. However, the data provided by us is without express or implied warranties,

and no commitments are made herein. If you need to use our products, we

recommend a series of tests. The application, use, processing or production of

products based on the technical information provided by us is outside our control and

therefore the responsibility lies with the user. Conditions and methods of handling,

storage, use or disposal of this product are beyond our control and may be beyond our

knowledge, and under no circumstances will we be liable for loss, damage or related

expenses arising from improper handling, storage, use or disposal of this chemical. For

more information, please review the technical safety specifications of our products or

contact our Marketing Services department.

Safety Information:

Catalyst, rinse with soapy water promptly after contact with skin. The staff can wear an

eye mask or safety glasses to achieve the purpose of eye protection. Eye washing and

bathing facilities should be available near the workplace. When working in places that

Newtop Chemical Materials (Shanghai) Co.,Ltd.

Technical Indicators

may come into contact with the product, you should pay attention to personal hygiene

and use detergent to wash the skin in contact with the product before eating, smoking

and leaving the work.

Shelf life:

Remain unopened for two years

Storage and Transportation:

Should be sealed, stored in a dry cool ventilated warehouse

Packing:

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper

ventilation. After the original packaging, please fasten the packaging cover as soon as

possible to prevent moisture and other substances from mixing and affecting the

product performance. Do not inhale dust and avoid contact between skin and mucous

membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and

change after work. Store contaminated clothes separately and use them after washing.

Practice good hygiene.

Technical support and business contacts E-mail: info@newtopchem.com

Mobile Phone: +0086-183 0190 3151 E-mail: info@newtopchem.com

Newtop Chemical Materials (Shanghai) Co.,Ltd. Technical Indicators

